

微型 | 电感式


M6




安装方式 [f / n f]	齐平	齐平	齐平	
感应距离 S_n [mm]	1.0mm	1.2mm	1.5mm	
型号	NPN N. O	LS-1.0M06N-K	LS-1.2M06N-K	LS-1.5M06N-K
	NPN N. C	LS-1.0M06N2-K	LS-1.2M06N2-K	LS-1.5M06N2-K
	PNP N. O	LS-1.0M06P-K	LS-1.2M06P-K	LS-1.5M06P-K
	PNP N. C	LS-1.0M06P2-K	LS-1.2M06P2-K	LS-1.5M06P2-K
待检测物体标准	铁 6×6×1mm	铁 6×6×1mm	铁 6×6×1mm	
修正系数	Fe37=1/不锈钢约0.85/黄铜约0.5/铝约0.45/铜约0.4			
设定距离 [mm]	0-0.8mm	0-0.96mm	0-1.2mm	
工作电压 [V]	10-30VDC			
最大负载电流 [mA]	200mA			
空载电流 [mA]	≤10mA			
电压降 [V]	<1.5VDC	<1.5VDC	<1.5VDC	
开关频率 [Hz]	2000Hz	2000Hz	2000Hz	
响应时间 [ms]	0.1ms/0.1ms	0.1ms/0.1ms	0.1ms/0.1ms	
磁滞 [S r 的百分比]	<15%			
重复精度 [S r 的百分比]	<1%			
环境温度 [°C]	-25 - +70°C			
温度漂移 [S r 的百分比]	<10%			
极性保护/短路保护	内置/脉冲			
过载保护电流 [mA]	220mA			
壳体材质	不锈钢			
感应面材质	POM			
开关状态显示	LED			
接线方式	150mm线缆（防油、耐折弯）+三针M8连接器			
防护等级	IP67			
抗冲击	30gn, 11ms			
抗震动	55Hz, 1mm ampl., 3×30min.			
EMC	IEC 60947-5-2			
配件	2个固定螺母			

尺寸图和接线图


单位: mm




NPN N. O



PNP N. O



NPN N. C



PNP N. C

