

1)标准电缆长度2m,
可供非标准电缆长度



CE

安装方式 [f / n f]	非齐平	非齐平	非齐平	
感应距离 S _n [mm]	4.0mm	8.0mm	10.0mm	
型号	NPN N. O	LN-04M12N-2S	LN-08M12N-2S	LN-10M12N-2S
	NPN N. C	LN-04M12N2-2S	LN-08M12N2-2S	LN-10M12N2-2S
	PNP N. O	LN-04M12P-2S	LN-08M12P-2S	LN-10M12P-2S
	PNP N. C	LN-04M12P2-2S	LN-08M12P2-2S	LN-10M12P2-2S
待检测物体标准	铁 12×12×1mm	铁 24×24×1mm	铁 30×30×1mm	
修正系数	Fe37=1/不锈钢约0.85/黄铜约0.5/铝约0.45/铜约0.4			
设定距离 [mm]	0-3.2mm	0-6.4mm	0-8.0mm	
工作电压 [V]	10-36VDC			
最大负载电流 [mA]	200mA			
空载电流 [mA]	≤10mA			
电压降 [V]	<1.5VDC	<2.0VDC	<2.0VDC	
开关频率 [Hz]	1000Hz	500Hz	400Hz	
响应时间 [ms]	0.2ms/0.2ms	0.3ms/0.3ms	0.5ms/0.5ms	
磁滞 [S r 的百分比]	<15%			
重复精度 [S r 的百分比]	<1%			
环境温度 [°C]	-25 - +70°C			
温度漂移 [S r 的百分比]	<10%			
极性保护/短路保护	内置/脉冲			
过载保护电流 [mA]	220mA			
壳体材质	铜镀镍			
感应面材质	PC			
开关状态显示	LED			
接线方式	2m线缆 (防油、耐折弯)			
防护等级	IP67			
抗冲击	30gn, 11ms			
抗震动	55Hz, 1mm ampl., 3×30min.			
EMC	IEC 60947-5-2			
配件	2个固定螺母			

尺寸图和接线图

单位: mm

